

# SikaGrout<sup>®</sup>-800

## DECLARATION OF PERFORMANCE No. 70369107

<b>1</b>	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:</b>	70369107
<b>2</b>	<b>INTENDED USE/S</b>	For uses in buildings and civil engineering works- Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete For uses subject to reaction to fire regulations
<b>3</b>	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
<b>5</b>	<b>SYSTEM/S OF AVCP:</b>	System 2+ System 3
<b>6a</b>	<b>HARMONISED STANDARD:</b>	EN 1504-3:2005
	Notified body/ies:	1139

### Declaration of Performance

SikaGrout<sup>®</sup>-800  
70369107  
2023.02 , ver. 2  
1029

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive strength	≥ 45 MPa	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0,05 %	System 2+	
Adhesive bond	≥ 2,0 MPa	System 2+	
Carbonation Resistance	Pass	System 2+	
Elastic Modulus	≥ 20 GPa	System 2+	
Thermal Compatibility	≥ 2,0 MPa	System 2+	
Capillary Absorption	≤ 0,5 kg·m <sup>-2</sup> ·h <sup>-0,5</sup>	System 2+	
Reaction to fire	Class A1	System 3	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski  
Function: Corporate Standardization  
and Approvals  
At Warsaw on 13 February 2023

Name : Maciej Pietrus  
Function: Standardization and Approvals  
At Cracow on 13 February 2023



End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

SikaGrout®-800  
70369107  
2023.02 , ver. 2  
1029



22

Sika Services AG, Zurich, Switzerland

70369107

Compressive strength	≥ 45 MPa
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 2,0 MPa
Elastic Modulus	≥ 20 GPa
Thermal Compatibility	≥ 2,0 MPa
Capillary Absorption	≤ 0,5 kg·m <sup>-2</sup> ·h <sup>-0,5</sup>
Reaction to fire	Class A1

EN 1504-3:2005

1139

For uses in buildings and civil engineering works- Structural and non structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete

For uses subject to reaction to fire regulations

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale..

### Declaration of Performance

SikaGrout®-800  
70369107  
2023.02 , ver. 2  
1029

3/4

BUILDING TRUST



**Sika Services AG**  
Tüffenwies 16  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Declaration of Performance**

SikaGrout®-800  
70369107  
2023.02 , ver. 2  
1029

**4/4**

**BUILDING TRUST**

