

# Sikagard® Wallcoat T

## DECLARATION OF PERFORMANCE

### No. 22580675

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	22580675
2	<b>INTENDED USE/S</b>	EN 1504-2:2004 Surface protection products – Coating Ingress protection (1.3) Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2)
3	<b>MANUFACTURER:</b>	Sika Deutschland GmbH Kornwestheimer Str. 103 - 107 70439 Stuttgart
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+ (for uses in buildings and civil engineering works)  System 3 (for uses subject to reaction to fire regulations)
6a	<b>HARMONISED STANDARD:</b>	EN 1504-2:2004
	Notified body/ies:	0921 0767

#### Declaration of Performance

Sikagard® Wallcoat T  
22580675  
04.12.2017 , ver. 2  
1008

**7 DECLARED PERFORMANCE/S** Tested system: Sikagard® WallCoat T (+ 5% water) + Sikagard® WallCoat T

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage:	NPD	System 2+	EN 1504-2:2004
Compressive strength:	NPD	System 2+	
Coefficient of thermal expansion:	NPD	System 2+	
Abrasion resistance (Taber test):	NPD	System 2+	
Cross cut:	NPD	System 2+	
Permeability to CO <sub>2</sub> :	s <sub>D</sub> > 50 m	System 2+	
Water vapor permeability:	Class I	System 2+	
Capillary absorption and permeability to water:	w<0,1 kg/(m <sup>2</sup> x h <sup>0,5</sup> )	System 2+	
Thermal compatibility:	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Chemical resistance:	NPD	System 2+	
Resistance to severe chemical attack <sup>2)</sup> :	Class I	System 2+	
Crack bridging ability:	NPD	System 2+	
Impact resistance:	Class I	System 2+	
Adhesion strength by pull off test:	≥ 1,0 (0,7) <sup>3)</sup> N/mm <sup>2</sup>	System 2+	
Reaction to fire:	B1	System 3	
Skid resistance:	NPD	System 2+	
Artificial weathering:	NPD	System 2+	
Antistatic behavior:	NPD	System 2+	
Adhesion to wet concrete:	NPD	System 2+	
Dangerous substances:	NPD	System 2+	

<sup>1)</sup> Please refer to the Sikafloor Chemical Resistance Chart

<sup>2)</sup> The value in brackets is the lowest accepted value of any reading.

**Declaration of Performance**

Sikagard® Wallcoat T  
 22580675  
 04.12.2017 , ver.2  
 1008

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name : Tomasz Gutowski  
Function: Corporate Standardization  
and Approvals  
At Warsaw on 02 February 2018

Name : Tatiana Ageyeva  
Function: Standardization and Approvals  
At Warsaw on 02 February 2018



.....

.....

---

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikagard® Wallcoat T  
22580675  
04.12.2017 , ver.2  
1008





08

EN 1504-2:2004

DoP No. 22580675

Sika Deutschland GmbH, Stuttgart

Notified Body 0921, 0767

Surface protection products – Coating: Ingress protection (1.3)  
Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2)

Permeability to CO <sub>2</sub> :	s <sub>D</sub> > 50 m
Water vapor permeability:	Class I
Capillary absorption and permeability to water:	w < 0,1 kg/(m <sup>2</sup> x h <sup>0,5</sup> )
Resistance to severe chemical attack:	Class I
Impact resistance:	Class I
Adhesion strength by pull off test:	≥ 1,0 (0,7)N/mm <sup>2</sup>
Reaction to fire:	B1

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


## FOR FURTHER INFORMATION:

Sika Deutschland GmbH  
Kornwestheimer Str. 103-107  
70439 Stuttgart

Telefon +49-711 80 09-0  
Telefax +49-711 80 09-321  
www.sika.de

## Declaration of Performance

Sikagard® Wallcoat T  
22580675  
04.12.2017, ver.2  
1008



**Declaration of Performance**  
Sikagard® Wallcoat T  
22580675  
04.12.2017 , ver.2  
1008

5/5

**BUILDING TRUST**

