

DECLARATION OF PERFORMANCE

Sika MonoTop-120 Seal no. 97911939

Click here to enter text.

1	UNIQUE IDENTIFICATION of the product-type:	97911939 Batch No. see packaging	
2	INTENDED USE	1 - component waterproofing mortar.	
	or uses of the construction product, in	Surface Protection Product – coating. Intended	
	accordance with the applicable harmonised	Use – Table ZA.1e of EN 1504-2:2004. Principles	
	technical specification, as foreseen by the manufacturer:	2, Methods 2.2 of EN 1504-9:2008.	
3	MANUFACTURER	Sika®	
	registered trade name or registered trade mark	Sika CZ, s.r.o.	
	and contact address of the manufacturer as	Bystrcká 1132/36	
	required under Article 11(5):	CZ-624 00 Brno	
4	AVCP	System 2+	
	System or systems of assessment and		
	verification of constancy of performace (AVCP)		
	or the construction product as set out in CPR,		
	Annex V:		
5	HARMONISED STANDARDS	EN 1504-2: 2004	
6	NOTIFIED BODY	Notified factory production control certification	
	In case of the declaration of performance	body TZUS Praha, s.p. No. 1020 performed the	
	(DoP)concerning a construction product	initial inspection of the manufacturing plant and	
	covered by a harmonised standard:	of factory production control and the continuou	
	·	surveillance, assessment and evaluation of	
		factory production control and issued the	

Declaration of Performance

Sika MonoTop-120 Seal 20.12.2018, Version no. 01 Identification nr. 97911939



certificate of conformity of the factory production control (FPC) 020025682.

7 **DECLARED PERFORMANCE**

Essential characteristics	Performance	AVCP	Harmonised technical specification
Linear shrinkage	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Adhesion by cross-cut test	NPD	System 2+	
Permeability to water vapour	Class I	System 2+	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/(m}^2 \text{ x h}^{0.5})$	System 2+	
Adhesion after thermal compatibility	NPD	System 2+	EN 1504-2:2004
Crack bridging ability	NPD	System 2+	
Pull-off test	≥ 1.0 (0,7) N/mm²	System 2+	
Fire Classification	A1	System 2+	
Slip/skid resistance	NPD	System 2+	
Artificial weathering	NPD	System 2+	
Antistatic behaviour	NPD	System 2+	
Dangerous substances	See MSDS	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner Position: Quality and EHS Manager

Position: General Manager SIKA CZ, s.r.o.

Brno, 20.12.2018

Name: Ing. Andrej Šišolák


End of information as required by Regulation (EU) No 305/2011

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika MonoTop-120 Seal 20.12.2018, Version no. 01 Identification nr. 97911939



9 CE MARKING



19

Sika CZ, s.r.o., Bystrcká 1132/36, 624 00 Brno, Factory 1180

DoP No. 97911939

EN 1504-2:2004

Notified Body 1020

Surface Protection Product – coating. Intended Use – Table ZA.1e of EN 1504-2:2004. Principles 2, Methods 2.2 of EN 1504-9:2008.

Permeability to water vapour Class I

Capillary absorption and permeability to water $w < 0.1 \text{ kg/(m}^2 \text{ x h}^{0.5})$ Pull-off test $\geq 1.0 (0.7) \text{ N/mm}^2$

Reaction to fire A1

http://dop.sika.com

$\label{prop:contact:} \textbf{For more information contact:}$

Sika CZ, s.r.o., Bystrcká 1132/36, CZ 624 00 Brno

tel: +420 546 422 464 Fax: +420 546 422 400 E-mail: sika@cz.sika.com

