

Sikagard[®]-675 W ElastoColor

DECLARATION OF PERFORMANCE

No. 0203030300100000031125

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	0203030300100000031125
2	INTENDED USE/S	1504-2:2004 Surface protection products – coating: Ingress protection (1.3) Moisture control (2.2) Increasing resistivity (8.2)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	1504-2:2004
	Notified body/ies:	0921

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage	NPD		1504-2:2004
Coefficient of thermal expansion	NPD		
Cross cut	Gt0	System 2+	
Permeability to CO2	$S_D \geq 50$ m	System 2+	
Water vapor permeability	$S_D \leq 5$ m (class 1)	System 2+	
Capillary absorption and permeability to water	$\omega \leq 0,1$ kg/m ² h ^{0.5}	System 2+	
Thermal compatibility (Freeze and thaw cycling with de-icing salt immersion)	≥ 1.0 (0,7) N/mm ² No bubbles, cracks or delamination	System 2+	
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Crack bridging ability	A1(+23°C)	System 2+	
Adhesion strength by pull-off test	≥ 1.0 (0,7) N/mm ²	System 2+	
Reaction to fire	Class E	System 2+	
Skid resistance	NPD		
Artificial weathering	Pass	System 2+	
Antistatic behavior	NPD		
Adhesion on wet concrete	NPD		
Dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
 Function: Corporate Standardization and Approvals
 At Warsaw on 25 May 2018

Name : Tatiana Ageyeva
 Function: Standardization and Approvals
 At Warsaw on 25 May 2018




End of information as required by Regulation (EU) No 305/2011





09

Sika Services AG, Zurich, Switzerland

DoP No. 0203030300100000031125

1504-2:2004

Notified Body 0921

Surface protection products – coating: Ingress protection (1.3), Moisture control (2.2), Increasing resistivity (8.2)

Cross cut	Gt0
Permeability to CO ₂	$S_D \geq 50$ m
Water vapor permeability	$S_D \leq 5$ m (class 1)
Capillary absorption and permeability to water	$\omega \leq 0,1$ kg/m ² h ^{0.5}
Thermal compatibility (Freeze and thaw cycling with de-icing salt immersion)	≥ 1.0 (0,7) N/mm ² No bubbles, cracks or delamination
Crack bridging ability	A1(+23°C)
Adhesion strength by pull-off test	≥ 1.0 (0,7) N/mm ²
Reaction to fire	Class E
Artificial weathering	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance
Sikagard®-675 W ElastoColor
0203030300100000031125
2018.05 , ver. 3
1125

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikagard®-675 W ElastoColor
0203030300100000031125
2018.05 , ver. 3
1125

4/4

Template for translation. Only for
internal use

BUILDING TRUST

