

SikaGrout®-312

DECLARATION OF PERFORMANCE 13886990

1	UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:	13886990
2	INTENDED USE/S	Anchoring Product (based on hydraulic cement) Method 4.2
3	MANUFACTURER:	Sika Österreich GmbH Bingser Dorfstraße 23 A-6700 Bludenz
4	AUTHORIZED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	2+ 3 (Reaction to fire)
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body:	1139

Declaration of performance

SikaGrout®-312

13886990

2017.10 , Vers. 01

1029

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	Harmonised Technical Specification
Pull out strength displacement	≤ 0.6 mm at load of 75 kN	EN 1504-6:2006
Chloride ion content	≤ 0.05 %	
Glass transition temperature	NPD	
Creep under tensile load	NPD	
Dangerous substances	See local safety data sheet	
Reaction to fire	Class A1	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Samuel Plüss
Function: Managing director
Bludenz 19 October 2017



Name : Rainer Planer
Function: Product Engineer
Bludenz 19 October 2017



End of information as required by Regulation (EU) No. 305/2011

DECLARATION OF PERFORMANCE

SikaGrout®-312
13886990
2017.10, Vers 01
1029



17

Sika Österreich GmbH, Bingser Dorfstraße 23, A-6700 Bludenz

DoP No. 13886990

EN 1504-6:2006

Notified body 1139

Anchoring Product
(based on hydraulic cement)
method 4.2

Pull out strength displacement	≤ 0.6 mm at load of 75 kN
Chloride ion content	≤ 0.05 %
Dangerous substances	See local safety data sheet
Reaction to fire	Class A1

dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data, copies of which can be found under www.sika.at.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which can be found under www.sika.at.

DECLARATION OF PERFORMANCE

SikaGrout®-312
13886990
2017.10, Vers 01
1029

SIKA ÖSTERREICH GMBH
Bingser Dorfstraße 23
A-6700 Bludenz
Österreich

DECLARATION OF PERFORMANCE
SikaGrout®-312
13886990
2017.10, Vers 01
1029

4/4

BUILDING TRUST

