
SikaGrout[®]-800

DECLARATION OF PERFORMANCE

No. 87191829

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	87191829
2	INTENDED USE/S	For uses in buildings and civil engineering works- Anchoring products for strengthening concrete by installing reinforcing steel (rebars) as covered in the scope of this standard For uses subject to reaction to fire regulations
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	SYSTEM/S OF AVCP:	System 2+ System 3
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	1139

Declaration of Performance

SikaGrout[®]-800
87191829
2022.12 , ver. 1
1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Pull-out strength	Displacement \leq 0.6 mm at load of 75 kN	System 2+	EN 1504-6:2006
Chloride ion content	\leq 0,05 %	System 2+	
Glass transition temperature	NPD	System 2+	
Reaction to fire	Class A1	System 3	
Durability/Creep under tensile load	NPD	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization and Approvals
At Warsaw on 07 December 2022

Name : Maciej Pietrus
Function: Standardization and Approvals
At Cracow on 07 December 2022



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaGrout®-800
87191829
2022.12 , ver. 1
1029



22

Sika Services AG, Zurich, Switzerland

87191829

Pull-out strength	Displacement \leq 0.6 mm at load of 75 kN
Chloride ion content	\leq 0,05 %
Reaction to fire	Class A1

EN 1504-6:2006

1139

For uses in buildings and civil engineering works- Anchoring products for strengthening concrete by installing reinforcing steel (rebars) as covered in the scope of this standard
For uses subject to reaction to fire regulations

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale..

Declaration of Performance

SikaGrout®-800
87191829
2022.12 , ver. 1
1029

3/4

BUILDING TRUST



Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

SikaGrout®-800
87191829
2022.12 , ver. 1
1029

4/4

BUILDING TRUST

