

Sika[®] Igoflex[®]-201

DECLARATION OF PERFORMANCE

No. 46192160

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	46192160
2	INTENDED USE/S	EN 15814:2011+A2:2014 Polymer modified bituminous thick coating (PMBC) intended for use for waterproofing in below ground structures PMB-CB2-W2A-C2A
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15814:2011+A2:2014
	Notified body/ies:	1023 0432 for reaction to fire

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Watertightness	Class W2A	System 3	EN 15814:2011+A 2:2014
Crack-bridging ability	Class CB 2	System 3	
Water resistance	No coloration of the water No changes in material	System 3	
Flexibility at low temperature	No cracks	System 3	
Dimensional stability at high temperatures	No sliding down	System 3	
Reaction to fire	Class E	System 3	
Resistance to compression	Class C2A	System 3	
Dangerous substances	NPD	System 3	
Durability of watertightness and reaction to fire	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization
and Approvals
At Warsaw on 01 July 2019

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 01 July 2019



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika® Icolflex®-201
46192160
2019.06 , ver. 2
1184

Template for translation. Only for
internal use



19

Sika Services AG, Zurich, Switzerland

DoP No. 46192160

EN 15814:2011+A2:2014

Notified Body 1023, 0432

Polymer modified bituminous thick coating (PMBC) intended for use for waterproofing in below ground structures
PMB-CB2-W2A-C2A

Watertightness	Class W2A
Crack-bridging ability	Class CB 2
Water resistance	No coloration of the water No changes in material
Flexibility at low temperature	No cracks
Dimensional stability at high temperatures	No sliding down
Reaction to fire	Class E
Resistance to compression	Class C2A
Durability of watertightness and reaction to fire	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika® Icolflex®-201
46192160
2019.06, ver. 2
1184

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sika® Icolflex®-201
46192160
2019.06 , ver. 2
1184

4/4

Template for translation. Only for
internal use

BUILDING TRUST

