

Sikagard[®]-700 S

DECLARATION OF PERFORMANCE

No. 0203030100100000011010

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	0203030100100000011010
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – hydrophobic impregnation: ingress protection (1.1), moisture control (2.1), increasing resistivity (8.1)
3	MANUFACTURER:	Sika Deutschland GmbH Kornwetheimer Straße 103-107 70439 Stuttgart Germany
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	0921

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Depth of penetration	Class I: < 10 mm	System 2+	EN 1504-2:2004
Water absorption and resistance to alkali			
Absorption ratio:	< 7.5 % compared with the untreated specimen	System 2+	
Absorption ratio:	< 10 % after immersion in alkali solution	System 2+	
Drying rate for hydrophobic impregnation	Class I: > 30 %	System 2+	
Loss of mass after freeze-thaw salt stress	Pass	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
 Function: Corporate Standardization and Approvals
 At Warsaw on 23 May 2018

Name : Tatiana Ageyeva
 Function: Standardization and Approvals
 At Warsaw on 23 May 2018




End of information as required by Regulation (EU) No 305/2011





08

Sika Deutschland GmbH, Stuttgart, Germany

DoP No. 0203030100100000011010

EN 1504-2:2004

Notified Body 0921

Surface protection product – hydrophobic impregnation: ingress protection (1.1), moisture control (2.1), increasing resistivity (8.1)

Depth of penetration	Class I: < 10 mm
Water absorption and resistance to alkali	
Absorption ratio:	< 7.5 % compared with the untreated specimen
Absorption ratio:	< 10 % after immersion in alkali solution
Drying rate for hydrophobic impregnation	Class I: > 30 %
Loss of mass after freeze-thaw salt stress	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance
Sikagard®-700 S
0203030100100000011010
2018.05 , ver. 1
1010

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikagard®-700 S
0203030100100000011010
2018.05 , ver. 1
1010

4/4

Template for translation. Only for
internal use

BUILDING TRUST

