

# Sikafloor®-25 PurCem® ECF

## DECLARATION OF PERFORMANCE

### No. 21757850

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	21757850
2	<b>INTENDED USE/S</b>	EN 1504-2:2004 Surface protection products – Coating Physical resistance (5.1) Chemical resistance (6.1)
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+ (for uses in buildings and civil engineering works)  System 3 (for uses subject to reaction to fire regulations)
6a	<b>HARMONISED STANDARD:</b>	EN 1504-2:2004
	Notified body/ies:	0086, 0833

#### Declaration of Performance

Sikafloor®-25 PurCem® ECF

21757850

2019.03 , ver. 2

1088

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage:	NPD	System 2+	EN 1504-2:2004
Compressive strength:	NPD	System 2+	
Coefficient of thermal expansion:	NPD	System 2+	
Abrasion resistance:	weight loss < 3000 mg	System 2+	
Cross cut:	NPD	System 2+	
Capillary absorption and permeability to water:	$w < 0,1 \text{ kg}/(\text{m}^2 \times \text{h}^{0,5})$	System 2+	
Thermal compatibility:	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Resistance to severe chemical attack:	Class II	System 2+	
Crack bridging ability:	NPD	System 2+	
Impact resistance:	Class III	System 2+	
Adhesion strength by pull off test:	$\geq 2.0 \text{ N}/\text{mm}^2$	System 2+	
Reaction to fire:	B <sub>fl</sub> -s1	System 3	
Skid resistance:	NPD	System 2+	
Artificial weathering:	NPD	System 2+	
Antistatic behavior:	NPD	System 2+	
Adhesion to wet concrete:	NPD	System 2+	
Dangerous substances:	NPD	System 2+	

### Declaration of Performance

Sikafloor®-25 PurCem® ECF  
 21757850  
 2019.03 , ver. 2  
 1088

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name : Tomasz Gutowski  
Function: Corporate Standardization  
and Approvals  
At Warsaw on 04 March 2019

Name : Tatiana Ageyeva  
Function: Standardization and Approvals  
At Warsaw on 04 March 2019



---

End of information as required by Regulation (EU) No 305/2011

**RELATED DECLARATION OF PERFORMANCE**

---

Product name	Harmonised standard	DoP number
Sikafloor®-25 PurCem® ECF	EN 13813:2002	33510462
Sikafloor®-25 PurCem® ECF	EN 1504-2:2004, EN 13813:2002	020814020020000012 1088

---

**Declaration of Performance**

Sikafloor®-25 PurCem® ECF  
21757850  
2019.03 , ver. 2  
1088



13

EN 1504-2:2004

DoP No. 21757850

Sika Services AG, Zürich, Switzerland

Notified Body 0086, 0833

Surface protection products – Coating: Physical resistance (5.1) Chemical resistance (6.1)

Abrasion resistance:	weight loss < 3000 mg
Capillary absorption and permeability to water:	$w < 0,1 \text{ kg}/(\text{m}^2 \times \text{h}^{0,5})$
Resistance to severe chemical attack:	Class II
Impact resistance:	Class III
Adhesion strength by pull off test:	$\geq 2.0 \text{ N}/\text{mm}^2$
Reaction to fire:	B <sub>fl</sub> -s1

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


## FOR FURTHER INFORMATION:

Sika Services AG  
Tüffenwies 16  
8048 Zürich

Telefon +41-58 436 40 40  
Telefax +41-58 436 53 54  
[www.sika.ch](http://www.sika.ch)

### Declaration of Performance

Sikafloor®-25 PurCem® ECF  
21757850  
2019.03 , ver. 2  
1088



**Declaration of Performance**  
Sikafloor®-25 PurCem® ECF  
21757850  
2019.03 , ver. 2  
1088

5/5

**BUILDING TRUST**

